# SYNTHETIC TURF OR NATURAL GRASS SPORTS FIELDS?

## WHAT ARE CONSTRUCTION COSTS?

### SYNTHETIC TURF

Single-field building costs range from **\$6.00-\$10.25/sq ft.** 

### NATURAL GRASS

Single-field building costs are dependent on soil used:
On-site native soil: \$0.60-\$1.50/sq ft
Native soil: \$1.50-\$3.00/sq ft
Sand cap: \$2.75-\$4.00/sq ft
Sand: \$5.50-\$8.00/sq ft

### SYNTHETIC TURF

**HOW HOT IS EACH SURFACE?** 

High surface temperatures are directly related to clear, sunny, and hot conditions. The **maximum surface temperature** recorded is **183°F.** 

### NATURAL GRASS

Surface temperatures rarely rise above 85°F, however, in dry conditions midsummer, temperatures have been recorded at 98°F.

### WHAT ARE MAINTENANCE COSTS?

# SYNTHETIC TURF

A K-12 School in Kansas spends \$6,800 on maintenance annually. Additionally, the field averages **360 labor hours**.

**Michigan State University** spends about **\$22,760** on maintenance and labor annually. The field averages **280 hours in labor**.

### NATURAL GRASS

A native soil field at a K-12 School in South Carolina spends roughly \$9,450 on maintenance annually. Additionally, the field averages 300 labor hours.

**Duke University** spends roughly **\$24,550** annually on maintenance and labor for a sand-based field. The field averages **480 hours in labor**.

# WHAT CAUSES FIELD HARDNESS AND WHAT IS THE THRESHOLD?

# SYNTHETIC TURF

Areas that lose infill, such as **inlays**, **painted areas**, **seams**, **and highuse areas** can have increased surface hardness. The values of **100 Gmax**\* (Clegg Impact Tester, ASTM 1702) and **164 Gmax**\* (ASTM F355 missile A) are the upper limits.

### **NATURAL GRASS**

Gmax\* of natural grass fields can vary greatly over short periods of time due to **changes in soil water content and the amount of field usage**. The same values of Gmax\* apply to natural grass fields.

\*Gmax is the value generated when testing surface hardness and provides an indication if a field is safe for play or if steps must be taken to reduce surface hardness. Gmax testing should occur annually, with more frequent testing suggested on heavily-used fields.

stma.org/institute Share f 💆 in